

## Equipment Specifications

Steam Logistics provides this information as general guidance related to equipment specifications. The exact size and weight limits will vary based on the equipment's manufacturer and the city, state, or federal jurisdiction where the equipment will pass. For specific guidance, please check with your Steam International Services Representative.

	Interior Dimensions			Door Openings		Capacity		Tare Weight
	Length	Width	Height	Width	Height	Volume	Weight	
20' standard	19' 4"	7' 8"	7' 10"	7' 8"	7' 6"	1,172 CFT	47,900 LBS	4,916 LBS
	232"	92"	94"	92"	90"	33.2 CBM	21,700 KGS	2,230 KGS
40' Standard	39' 5"	7' 8"	7' 10"	7' 8"	7' 6"	2,390 CFT	59,040 LBS	8,160 LBS
	473"	92"	94"	92"	90"	67.7 CBM	26,780 KGS	2,230 KGS
40' High Cube	39' 5"	7' 8"	8' 10"	7' 8"	8' 5"	2,694 CFT	58,450 LBS	8,750 LBS
	473"	92"	106"	92"	101"	76.3 CBM	26,510 KGS	3,970 KGS
45' High Cube	44' 6"	7' 8"	8' 10"	7' 8"	8' 5"	3,050 CFT	64,250 LBS	8,550 LBS
	534"	92"	106"	92"	101"	86.4 CBM	29,140 KGS	3,880 KGS
20' Reefer	17' 8"	7' 5"	7' 5"	7' 5"	7' 3"	1,000 CFT	45,760 LBS	7,040 LBS
	212"	89"	89"	89"	87"	28.3 CBM	20,800 KGS	3,200 KGS
40' Reefer	37' 8"	7' 5"	7' 2"	7' 5"	7' 0"	2,040 CFT	56,272 LBS	10,780 LBS
	452"	89"	86"	89"	84"	57.8 CBM	25,580 KGS	4,900 KGS
40' HC Reefer	37' 11"	7' 6"	8' 2"	7' 6"	8' 0"	2,344 CFT	57,561 LBS	9,900 LBS
	455"	90"	98"	90"	96"	66.6 CBM	25,980 KGS	4,500 KGS
20' Open Top	19' 4"	7' 7"	7' 8"	7' 6"	7' 2"	1,136 CFT	47,320 LBS	5,280 LBS
	232"	56"	92"	90"	86"	32.23 CBM	21,600 KGS	2,400 KGS
40' Open Top	39' 5"	7' 8"	7' 8"	7' 8"	7' 5"	2,350 CFT	58,710 LBS	8,490 LBS
	473"	92"	92"	92"	89"	67.5 CBM	26,630 KGS	3,850 KGS
20' Flat Rack	18' 5"	7' 3"	7' 4"	N/A	N/A	N/A	47,333 LBS	5,578 LBS
	221"	87"	88"	N/A	N/A	N/A	21,470 KGS	2,530 KGS
40' Flat Rack	39' 7"	6' 10"	6' 5"	N/A	N/A	N/A	85,800 LBS	12,081 LBS
	475"	82"	77"	N/A	N/A	N/A	39,000 KGS	5,480 KGS
20' Collapsible Flat Rack	18' 6"	7' 3"	7' 4"	N/A	N/A	N/A	61,117 LBS	6,061 LBS
	222"	87"	88"	N/A	N/A	N/A	27,730 KGS	2,750 KGS
40' Collapsible Flat Rack	39' 7"	6' 10"	6' 5"	N/A	N/A	N/A	85,800 LBS	12,787 LBS
	475"	82"	77"	N/A	N/A	N/A	39,000 KGS	5,800 KGS
20' Platform	19' 11"	8' 0"	7' 4"	N/A	N/A	N/A	52,896 LBS	6,061 LBS
	239"	96"	88"	N/A	N/A	N/A	24,000 KGS	2,750 KGS
40' Platform	40' 0"	8' 0"	6' 5"	N/A	N/A	N/A	86,397 LBS	12,783 LBS
	480"	96"	77"	N/A	N/A	N/A	39,200 KGS	5,800 KGS